

# SEMI-CONDUCTIVE NON-WOVEN 4771



Semi-Conducting non woven tapes primary function is to equalize the field current around the conductor or core and to ensure electrical contact with the earthing system. This reduces the electrical stress on the insulation material and enhances performance. They can also be used to prevent electrolytic corrosion of metallic armour layers.

## BENEFITS

- Good bedding performance
- Good conductive properties
- Strong material

## APPLICATIONS

- ESD lining
- EMI shielding of cables
- Shielding and electric field control

## ORDER EXAMPLE

Part number	Thickness (mm)	Width (mm)
4771	<b>0.15 : 0.15 mm</b> <b>0.18 : 0.18 mm</b> <b>0.30 : 0.30 mm</b> <b>0.50 : 0.50 mm</b>	Specify the width in mm
Length (mm)	Adhesive	
Specify the length in mm	<b>1 : Standard self-adhesive</b> <b>2 : Without self-adhesive</b> <b>3 : With conductive self-adhesive</b>	

## TECHNICAL SPECIFICATION AND PART NUMBERS

Properties	4771-0.15	4771-0.18	4771-0.30	4771-0.50	Test method
Thickness (mm)	0.15	0.18	0.30	0.50	ISO 9073-2
Mass per unit area (g/m <sup>2</sup> )	100	65	60	95	ISO 9073-1
Tensile strength (N/cm)	60	35	35	60	ISO 9073-3
Elongation (%)	13	13	13	14	ISO 9073-3
Specific length resistivity (Ωcm)	5	800	800	600	DIN 54345 Part 5
Volume resistivity (kΩcm)	10	25	10	10	DIN 54345 Part 1
Service temperature (°C)			< 140		IEC 60216 (TIS 045)
Processing temperature (°C)			< 225		(TIS 045)
Composition			Polyester Polycrylate Carbon impregnation		
Max. width			960 mm		

These values are measured under laboratory conditions.  
In other situations results may differ. Please read our Guarantee.